

# PORCELAIN WOOD



Product displayed is Ashdown Ash

## Ashdown

Inspired by the exotic nature of African zebrawood and the earthy warmth of Mediterranean olive trees

21.8 x 89.3cm (8.6 x 35.2 inches)

  11.5mm thickness



Ashdown Aged



Ashdown Ash



Ashdown Cherry



Ashdown Coast



Ashdown Olive

Product displayed is Ashdown Cherry



## Ashdown

Technical Characteristics		Reference standard
Manufacture process	Single-firing	Dry pressed ceramic tile
Thickness (mm.)	11.5	UNE EN ISO 10545 Part 2
Length, width, thickness, side straightness, orthogonality, flatness.	Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B la	UNE EN ISO 10545 Part 2
Water absorption	E < 0.5 %	UNE EN ISO 10545 Part 3
Flexion resistance N/sq. mm. and breaking strength	> 35 > 1300	UNE EN ISO 10545 Part 4
Resistance to surface abrasion (Glazed tiles)	Available on request	UNE EN ISO 10545 Part 7
Lineal thermic dilatation	< $9 \cdot 10^{-6} / ^\circ \text{C}$	UNE EN ISO 10545 Part 8
Thermic impact resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 9
Cracking resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 11
Frost resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 12
Slip resistance	Class 1	UNE ENV 12633:2003

## Chemical resistance

Domestic cleaning products	Type GA	UNE EN ISO 10545 Part 13
Swimming pool salt	Type GA	
Acids and bases (low concentration)	Minimum Type GLB	
Stains resistance	Minimum Type 4	UNE EN ISO 10545 Part 14

# PORCELAIN WOOD



Product displayed is Ashdown Olive

T +44 (0) 844 854 3050 E

E [ask@porcelainwood.com](mailto:ask@porcelainwood.com)

[www.porcelainwood.com](http://www.porcelainwood.com)