

PORCELAIN WOOD



Whinfell

Product displayed is Whinfell Dark

Available in vivid light and dark grains and at the cutting-edge of contemporary, our Whinfell range is a statement in itself

14.4 x 89.3cm (5.7 x 35.2 inches)



11.5mm thickness



Whinfell Dark



Whinfell Light

21.8 x 89.3cm (8.6 x 35.2 inches)



11.5mm thickness



Whinfell Dark



Whinfell Light

44.3 x 89.3cm (17.4 x 35.2 inches)



11.5mm thickness



Whinfell Dark




Whinfell Light


cut and bevelled skirting tile
9.4 x 44.3 cm / 3.7 x 17.4 inches
Whinfell-CR



staircase step
44.3 x 89.3 cm / 17.4 x 35.2 inches
Whinfell-CR



step lip
44.3 x 89.3 cm / 17.4 x 35.2 inches
Whinfell-CR



The staircase step and gradone can be sold with or without the ribbed notch. Angle is also available.

Whinfell

| Technical Characteristics | | Reference standard |
|---|--|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Thickness (mm.) | 11.5 | UNE EN ISO 10545 Part 2 |
| Length, width, thickness, side straightness, orthogonality, flatness. | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B la | UNE EN ISO 10545 Part 2 |
| Water absorption | E < 0.5 % | UNE EN ISO 10545 Part 3 |
| Flexion resistance N/sq. mm. and breaking strength | > 35 > 1300 | UNE EN ISO 10545 Part 4 |
| Resistance to surface abrasion (Glazed tiles) | Available on request | UNE EN ISO 10545 Part 7 |
| Lineal thermic dilatation | < $9 \cdot 10^{-6} / ^\circ \text{C}$ | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Conforms to industrial standard | UNE EN ISO 10545 Part 9 |
| Cracking resistance | Conforms to industrial standard | UNE EN ISO 10545 Part 11 |
| Frost resistance | Conforms to industrial standard | UNE EN ISO 10545 Part 12 |
| Slip resistance | Class 1 | UNE ENV 12633:2003 |

Chemical resistance

| | | |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products | Type GA | UNE EN ISO 10545 Part 13 |
| Swimming pool salt | Type GA | |
| Acids and bases (low concentration) | Minimum Type GLB | |
| Stains resistance | Minimum Type 4 | UNE EN ISO 10545 Part 14 |

PORCELAIN WOOD

